




MAG-MIFAB

Access Panels




The **MIFAB® UA** is a multipurpose access door. It is designed for flush installation in drywall, block or tile, walls and ceilings. Frame features rounded safety corners, concealed hinge, flush with frame fit. It has a unique white finish. Door is formed for rigidity and safety.

The **MIFAB® MPFR** fire rated access door is fire rated by Underwriters Laboratories Inc., for 1½ hours, "B" label in walls and is rated by Warnock Hersey for 2 hours in ceilings. The door meets ANSI-UL 10B standards. The same door can be used in walls and ceilings.



The **MIFAB® CAD** recessed access door is designed for use in acoustical, drywall, or tiled surfaces. The door panel is recessed 5/8" to allow the insertion of various types of material. Only the thickness of the door and frame edges are exposed. It has a unique white finish.

The **MIFAB® CAD-FL** access door is designed for flush installation in a drywall or plaster surface. The door panel is flush with the frame. When installed flush with the wall or ceiling only the door panel is exposed. A mounting bracket is recessed 5/8" from the door. It has a unique white finish.





FEATURES & BENEFITS

- > Unique white finish
- > Rigid engineered construction
- > Rounded safety corners
- > Custom sizes available
- > Stainless steel available
- > Specialty locks available


The **MIFAB® MDW** access door is designed for installation after the drywall has been applied and when a concealed outer flange is required.

The outer frame has a galvanized drywall taping bead. Drywall cement can be applied over the beading at the same time as the wallboard joints and corners. Only the door is visible. It has a unique white finish.



The **MIFAB® CAD-FL-PL** recessed door is designed for flush installation in a drywall or plaster surface. The door panel is flush with frame. When installed flush with the wall or ceiling, only the door panel is exposed. A 3" wide metal lathe on all sides provides a rigid frame. A mounting bracket is recessed 5/8" from the door. It has a unique white finish.

The **MIFAB® MI-VB** valve box is designed for flush installation into walls to house valves and pipes.



The **MIFAB® PLASTIC SNAP-IN PANEL**